

Description

The pH SmartSync® is a sensor-mount transmitter for pH sensors. The transmitter's output is Modbus RTU. The transmitter can be configured by means of a wireless Bluetooth interface with the iQuickView® app.

Purchase Information

Part Number	T100-01
Description	pH Transmitter, Modbus RTU Output

Classification

Model Type	T100
Product Type	Transmitter

Specifications

Measurement

Type	pH
Principle	Potentiometric Sensor Input
Range	0–14 pH
Drift	Not applicable

Operational Range

Temperature	0–55 °C [32–131 °F]
Pressure	Not applicable
Flow Rate	Not applicable

Signal

Input	Millivolts
Output	Modbus RTU

Sterilization

Autoclavable	Not applicable
Steam Sterilizable	Not applicable
Gamma Sterilizable	Not applicable

Connectors and Cables

Connector A (Input)	VP8 Variopin, 8-pin Threaded Plug
Connector B (Output)	M12-5
Cable Length	Not applicable

Process Interface

Insertion Method	Not applicable
Insertion Length	Not applicable

Wetted Materials

Not applicable



T100-1 pH SmartSync®



Packaging and Regulations

Packaging Information

Package Type	Cardboard box
Package Dimensions	20.32 cm x 10.16 cm x 5.72 cm [8 in x 4 in x 2.25 in]
Package Weight	< 0.5 kg [1 lb]
Double Bagged	No
Cleanroom Bagged	No
Cleanroom Class.....	Not applicable
Storage Conditions.....	Temperature: 5–50 °C [41–122 °F]
Included Accessories	Not applicable
Quality Certificate	Included
Shelf Life	Not applicable
Shelf Life Post Gamma Sterilization	Not applicable

Origination and Tariff Code

Harmonized Tariff Trade Code.....	9027803100
Country of Origin	USA
MFR Location	California, USA

Purchasing Information

Unit of Sale.....	Each
Minimum Purchase Quantity	Each

Regulatory and Compliance

CE Compliant	Yes
RoHS Compliant	Yes
REACH Compliant	Yes
CFR 21-11 Compliant	Not applicable
BSE/TSE/ADI Compliant.....	Not applicable
USP Class VI Compliant	Not applicable
FDA Material Compliant	Not applicable

The contents of this publication are presented for information purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding products or services described herein or in their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the design or specification of such products at any time.

Doc Nbr: PDS-112002 R3 Published 28 Feb 2022
© February 2022 Broadley-James Corporation. All rights reserved. Visit www.broadley-james.com/trademarks for trademark information.

TMP-PSS-102101 R1



North America and Pacific

Email: sales@broadleyjames.com
Web: www.broadleyjames.com

Phone: 949-829-5555
Toll-free: 800-288-2833
Fax: 949-829-5560

19 Thomas, Irvine, CA, 92618 USA

United Kingdom and EU Countries

Email: sales@broadleyjames.co.uk
Web: www.broadleyjames.eu

Phone: +44 (0)1525 862518
Fax: +44 (0)1525 862811

Wrest Park, Silsoe, Bedford MK45 4HS, UK