

Description

The SingleSense® Model SU800 Single-Use pH Sensor is gamma irradiation compatible and designed for pre-installation into a bioprocess container (BPC) via a 1-inch hose barb port. The sensor can be used for upstream and downstream BPC applications including media mixing, buffer preparation, and cell culture in single-use bioreactors.

Model	SU800
Part Number	SU800-16-V8

Sensor Specifications

Type	pH
Measurement Principle	Potentiometric
Output Signal	Analog
Measurement Range	2 - 11 pH
Operating Temperature	4°C - 50°C [39°F - 122°F]
Max Pressure	15 psig
Shelf Life	36 months
Gamma Tolerance Level	50 kGy
Process Connection	1-inch hose barb
Sensor Connector	8-pin Variopin

Wetted Materials

Main Sensor Body	PEEK, USP class VI, USP 87, ADI free
Port Gasket	Dimethyl silicone rubber Pt cure, USP Class VI, USP 87, ADI free
O-ring	EPDM, USP class VI, USP 87, FDA compliant extraction tested 21 CFR 177, ADI free
pH Glass Electrode	Lead-free glass
Ceramic Junction	Alumina silicate

Regulatory Compliance

USP Class VI	Yes, all wetted parts
REACH Compliant	Yes
RoHS Compliant	Yes
BSE/TSE/ADI Free	Yes



SU800-16-V8 Single-Use pH Sensor

Packaging Information

Package Type Cardboard box with double-bagged sensor inside
Package Dimensions 20.32 x 8.89 x 5.72 cm [8 x 3.5 x 2.25 in]
Package Weight < 0.5 kg [1 lb]
Double Bagged Yes, sensor is double-bagged
Cleanhood Bagged Yes, inner bag only
Cleanhood Class Class 7 Clean Air Hood
Storage Conditions Temperature: 5° - 35° C [41° - 95° F]
Included Accessories Not applicable
Quality Certificate Included

Origination

Country of Origin USA
MFR Location California, USA

Purchasing Information

Unit of Sale Each
Minimum Purchase Quantity Each

The contents of this publication are presented for information purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding products or services described herein or in their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the design or specification of such products at any time.

Doc Nbr: PDS-112007 R9
© April 2026 Broadley-James Corporation. All rights reserved. Visit www.broadleyjames.com/IP for trademark and patent information.

TMP-PDS-112001 R3



North America and Pacific

Email: sales@broadleyjames.com
Web: www.broadleyjames.com

Phone: +1-949-829-5555
Fax: 1-949-829-5560

19 Thomas, Irvine, CA, 92618 USA

United Kingdom and EU Countries

Email: sales@broadleyjames.co.uk

Phone: +44 (0)1525 862518

Wrest Park, Silsoe, Bedford MK45 4HS, UK